



**KEY FEATURES**

- Full HD Resolution**
- H.264 Compression**
- Dual Streaming**
- Digital PTZ**
- Upto 6Mpxl Support**
- Support Analytics**

**OPTIONAL FEATURE**



**DETECTS 3 FACES AT A TIME**

**SPECIFICATIONS**

**Intelligent Features**

- LCD Display
- Operation System
- Pentaplex function
- Control Mode
- IP Camera Input

**Decoding Capability**

- Protocol
- Standard

**Output**

- Output
- Two-way Talk
- IP Resolution
- Resolution
- Frame
- Tour Display
- Status Display
- Privacy Masking
- Video Compression
- Audio Compression
- Image Encoding
- Dual Stream
- Recording Mode
- Time bar
- Trigger Events
- Motion Detection
- Capture
- Alarm Input
- Alarm Output
- Max Playback
- Backup Mode
- Ethernet
- Network protocol
- Network Functions
- Remote Operation
- Smart Phone
- Hard Disk
- HDD Management
- USB Interface
- RS485
- Power Supply
- Power Consumption
- Working Environment
- Dimension(W\*D\*H)
- Weight
- Installation

**P2P function**

**Cloud Storage**

**AU-NX2004**

1ch. Face detection tracks 3 people face at the same time or 2ch. Perimeter Intrusion detection, up to 4 rules.  
Displays DVR IP address, inner temperature, error code, HDD number, Network status etc

**Embedded LINUX**

Live monitoring, recording, playback, backup & remote access

Front panel, USB mouse, IR remote control, Network

4ch.(40Mbps)

4ch.D1@30fps

4ch.720P@30fps

4ch.1080P@30fps

**Onvif**

PAL (625line, 50f/s) NTSC (525line, 60f/s)

1 CVBS, BNC (1.0Vp-p,75 ohms)

1 HDMI, 1.3a,support 1920×1080 Resolution

1 VGA,1920×1080,1440×900,1280×1024,1024×768,800×600 Resolution

1 BNC (2.0Vp-p,300 ohms)

1ch. Standalone

Main stream:up to 5632×4224, Auxiliary stream:4CIF

5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF

1~30fps

Support

LCD,blue backlight(working temperature,recording status,error code etc.)

Four zones for privacy masking for each channel

MPEG-4/H.264(High Profile@Level4.2)

G.711A

Adjustable encoding quality, variable code stream/fixed code stream

Support

Manual, auto, motion detection, stop

Support

Recording, PTZ, Tour,Email

396 (22×18) detection zone, variable sensitivity levels

JPEG capture

4ch.

3ch.NO,NC

1/2/4 ch.

USB,HDD,Network Backup

1 RJ-45 port (10M/100M/1000M)

TCP/IP, UDP, HTTP, RTP/RTSP

DHCP, PPPoE, DDNS,SMTP,SNTP,FTP,UPnP,P2P,3G

Monitoring,PTZ control,playback,system setting,file download,log information

iPhone,iPad,Android

1 SATA ports,each SATA supports 6TB

Hard disk hibernation technology, HDD faulty alarm&raid

2 USB 2.0 ports

Standard 485, half duplex,PTZ control

DC12V/3.3A

6W (without HDD&POE)

-10℃~+55℃ / 10% - 90%RH

1U, 360x260x48 (mm)

2Kg (without HDD)

Desk type

Realize remote monitoring, playback and control like IE Web login. No need any network, IP setting, easy for end user to use network function.

Support Dropbox and Google Drive