


Full HD Network Video Recorders
AU-NX3000 Series



KEY FEATURES



■ DETECTS 3 FACES AT A TIME

SPECIFICATIONS

	AU-NX3008	AU-NX3016	AU-NX3032
Intelligent Features	1ch. Face detection tracks 3 people face at the same time or 2ch. Perimeter Intrusion detection, up to 4 rules.		NO
LCD Display	Displays DVR IP address, inner temperature, error code, HDD number, Network status etc		
Operation System	Embedded LINUX		
Pentaplex function	Live monitoring, recording, playback, backup & remote access		
Control Mode	Front panel, USB mouse, IR remote control, Network		
IP Camera Input	8ch.(80Mbps) 8ch.D1@30fps 8ch.720P@30fps 6ch.1080P@30fps	16ch.(160Mbps) 16ch.D1@30fps 13ch.720P@30fps 6ch.1080P@30fps	32ch.(200Mbps) 16ch.D1@30fps 13ch.720P@30fps 6ch.1080P@30fps
Decoding Capability			ONVIF
Protocol	PAL (625line, 50f/s) NTSC (525line, 60f/s)		
Standard	1 CVBS, BNC (1.0Vp-p, 75 ohms)		
Output	1 HDMI, 1.3a, support 1920×1080 Resolution		
Output	1 VGA, 1920×1080, 1440×900, 1280×1024, 1024×768, 800×600 Resolution		
Two-way Talk	1 BNC (2.0Vp-p, 300 ohms)		
IP Resolution	1ch. Standalone		
Resolution	Main stream: up to 5632×4224, Auxiliary stream: 4CIF		
Frame	5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF		
Tour Display	1~30fps		
Status Display	Support		
Privacy Masking	LCD, blue backlight (working temperature, recording status, error code etc.)		
Video Compression	Four zones for privacy masking for each channel		
Audio Compression	MPEG-4/H.264 (High Profile@Level4.2)		
Image Encoding	G.711A		
Dual Stream	Adjustable encoding quality, variable code stream/fixed code stream		
Recording Mode	Support		
Time bar	Manual, auto, motion detection, stop		
Trigger Events	Support		
Motion Detection	Recording, PTZ, Tour, Email		
Capture	396 (22×18) detection zone, variable sensitivity levels		
Alarm Input	JPEG capture		
Alarm Output	8ch.		
Max Playback	3ch.NO, NC		
Backup Mode	USB, HDD, Network Backup		
Ethernet	1 RJ-45 port (10M/100M/1000M)		
Network protocol	TCP/IP, UDP, HTTP, RTP/RTSP		
Network Functions	DHCP, PPPOE, DDNS, SMTP, SNTP, FTP, UPnP, P2P, 3G		
Remote Operation	Monitoring, PTZ control, playback, system setting, file download, log information		
Smart Phone	iPhone, iPad, Android		
Hard Disk	2 SATA ports, each SATA supports 4TB		
HDD Management	Hard disk hibernation technology, HDD faulty alarm & raid		
USB Interface	2 USB 2.0 ports		
RS485	Standard 485, half duplex, PTZ control		
Power Supply	DC12V/3.3A		
Power Consumption	10W (without HDD&POE)		
Working Environment	-10°C (~+55°C / 10% ~ 90% RH)		
Dimension(W*D*H)	1U, 360x260x48 (mm)		
Weight	2Kg (without HDD)		
Installation	Desk type		
P2P function			
Cloud Storage	Realize remote monitoring, playback and control like IE Web login. No need any network, IP setting, easy for end user to use network function.		
	Support Dropbox and Google Drive		